

New Compact Cash Drawer

The C2120 compact cash drawer is distinguished by a combination of a small footprint and a large capacity. It perfectly fits with the new generation of POS systems, which are likewise characterized by their small space requirement. The C2120 offers sophisticated operation and a high standard of security.

Be it on a simple cash register or intelligent DN SeriesTM BEETLE system, the cash drawer is one of the most important peripherals of a POS system. After all, cash, checks, credit card slips, coupons and other checkout documents must be stored securely and in sufficient quantities. National, international and sector specific requirements and the different designs and functionalities of the individual items of POS furniture also must be taken into account.



The Diebold Nixdorf C2120 compact cash drawer is a low-priced entry-level cash drawer with a large capacity. The width of the banknote compartments can be adjusted variably to adapt them to different sizes of notes (currencies). The coin tray can be removed to reveal an additional compartment for banknotes, checks and documents. The cash drawer opens outwards at the front as far as the coin compartment area under software control. It can then be pulled out manually as far as it is necessary for working and moves extremely smoothly. The cash trays can be completely removed from the C2120 compact cash drawer and optionally be equipped with a lockable cash tray cover.

Connection concepts

The C2120 compact cash drawer can be connected directly to the intended cash drawer port of the DN Series BEETLE system family and to the DN Series POS printers with a cash drawer interface (RJ12).

Cash compartments

- 8 large coin compartments / insert (4 variable in width) / insert removable
- 4 or 5 note compartments, variable tray
- Tray for checks, documents





Specification

Direction of travel at opening

• To the front

Opening type

• Electronic

Key

No. of coin compartments

• Size adjustable: 8 / 4

No. of note compartments

• Size adjustable: 4 / 4 or 5 /5

Additional compartments for checks, documents, notes

• (below the coin insert): 1

Lock / Keyings

• Yes / 1

Emergency opening facility

• Yes

Cash drawer interface

Operating voltage: 24 V +/-10%
Opening pulse current: max. 1A
Opening pulse duration: 80 ... 120 ms

Connector combinations, cable lengths

• RJ12 - RJ12

• - 3.0 m included

• - 5.0 m optional

Dimensions

Depth: 418 mmWidth: 413 mmHeight: 100 mm

Weight

• 6.6 kg

Color options

Black

Environmental Conditions

- \bullet Operating temperature 0 °C to 40 °C, max. 80% RH
- Storage temperature -25 °C to 65 °C, max. 90% RH
- Relative humidity 10% to 90% RH (no condensation)

Options:

- Lockable cover for insert tray
- Additional insert trays







